



HTC Park 4M

Technical Specification

Specification	CE Approved (Conforms to BS 6571)
Maximum Boom Length	4M
Opening/Closing Time	2-4.0 Seconds (depends on arm length)
Power Supply	Single Phase 240v, 6 Amp
Duty Cycle	100% Continuously Rating
Arm Diameter	85mm by 60mm Oval
Rest	Fixed end post or swinging leg
Finish	Two pack epoxy coated
Colour	Orange, Blue, Grey, Red other colours available
Override	Handle override on power failure (inside cabinet)
Warranty	12 months parts and labour

The Park Mini barrier system has been designed to offer continuous operation for small car parks and distribution entrances. We have installed lots on traffic islands and at the side of security lodges, they control up to 4m roadway and can work without end rests.

Using a new IP compatible control panel it gives us lots of functions, including event display of the last 800 cycles.

The barrier arm is controlled via a three phase inverter driven motor and gearbox, which ensures a smooth consistent operation.

The control panel and motor is housed within the aesthetically designed 380x360 aluminium housing, giving us lots of space to add our wide range of access control systems.

Safety Equipment as Standard

All our barrier systems come factory fitted with a set of photocells and resistive underside edge, for pedestrian safety. Traffic barrier systems are not designed for pedestrian use, only vehicular. We also fit as standard on installation a safety induction loop, this detects any vehicle that drives through the barrier and prevents it from lowering.

We also fit an audible warning sounder on the cabinet, which makes users and general public alike when the barrier is in operation. Due to the smooth and near silent operation of the barrier, this is required.



Optional Extras and Accessories

- Built in LED lights housed within the arm
- Aluminium bottom skirt
- Aluminium top and bottom skirt
- Additional solenoid locking
- GSM, Wireless and Wifi Intercom Systems
- Proximity and keypad controls
- Radio remote controls
- Dial to open solutions
- Car height posts
- HGV height posts

0800 2100 624

www.hiteccontrols.com

