

## ML SOLO PLUS

## 4G LTE INTERCOM SPECIFICATION

### FEATURES AND BENEFITS



- 316 marine grade stainless steel faceplate
- High strength, alloy cast back box
- LED downlight
- 40mm low profile backbox
- Stainless steel security screws
- Surface or flush mounted\*
- Downward facing microphone
- **THS** Horwood quality sound
- Call up to 8 numbers from a single call point
- 7 programmable colours
- IP 65 rated
- Time clock with 9 profiles
- 2 year warranty
- Backlit, vandal resistant keypad
- Timed trade button and clear button
- 400 pin codes for coded entry

H 224 x W 96 x D 40

\*Stainless Steel Only

### DOWNLOAD THE COMMTTEL 'COMMAND ONE' APP



**OPEN | HOLD | CLOSE**  
**AT THE CLICK OF A BUTTON**

[www.telguard.co.uk/support/downloads/apps.html](http://www.telguard.co.uk/support/downloads/apps.html)

### EASY TO USE

- The single call button can ring through to up to 8 cascading landline or mobile phone numbers. Once answered, if the recipient wants to grant access to the visitor they simply press the # key on their phone.

### DOWNLOADABLE ACTIVITY LOGS

- Download the last 10,000 interactions with the unit and see who is gaining entry, how and when. A great security feature for free.

### DIAL TO OPEN

- Authorise up to 900 numbers the ability to call the unit and open your door/gate. A modern and more cost effective alternative to traditional access control.

### EASY TO INSTALL

### TWO YEAR WARRANTY

### SPECIFICATIONS

- **Power** 12 Volt 1 Amp. DC PSU fitted with a 3A fuse (supplied and must be dedicated to the Telguard intercom unit). Power Consumption: 120 mA Idle @ 12 Volts.
- **Telephone Type** Standard DTMF (Dual Tone Multi Frequency) generating telephone, cordless or mobile phone.
- **Programming** Remotely programmable via App, SMS or via GSM modem. Locally via USB cable.
- **Relays** 3: 1 x 2A, 2 x 200mA, 2 x Auxiliary inputs.
- **Relay Activation Time** 1 – 60 seconds, adjustable locally and remotely.
- **Operating Commands** Default #, 2#, 3#, 4#, 5#, 6#, 7#, 8#, 9#. All relay commands are configurable.
- **Time Clocks** This utilizes the on board time clock enabling custom profile functions to be activated.
- **Authorised Call Access** 900 telephone numbers can be stored. Calling the unit, from an authorised telephone number activates the relay.



Raising Standards  
Safety Assured



EU CE Declaration of Conformity and Radio Equipment Directive is available at [www.commtel-uk.com](http://www.commtel-uk.com) | GB-RH10 9XN